Certificate of Compliance

You have been awarded:

Intertek WH US Mark for Category D - Door/frame Assemblies

Standards: UL 10(c) (2016)

Certificate number: WHI22-28731446

This is a certificate of compliance to certify that the bearer has successfully completed the requirements of the above scheme which include the testing of products, the initial assessment, and are subject to continuing annual assessments of their compliance and testing of samples of products taken from production (as applicable to the scheme) and has been registered within the scheme for the products detailed.

Organization: ARFAD International Industry Company
Building No. 4177, Road 118, 3rd Industrial Area
Al Jubail 35729
Kingdom of Saudi Arabia

Product: Strebord 44 core - Single Leaf Door Assembly - 20 Minutes Without Hose Stream - UL 10C
Spec ID: 46757
Fire Rating: 20 Min w/out Hose Positive Pressure
Listing Information: See following page(s)

Certification body: Intertek Testing Services NA, Inc.
Initial registration: October 22, 2022
Date of expiry: December 31, 2026
Issue status: 5

Authorized By: _____
Jean-Philippe Kayl, Director of Certification

Intertek Testing Services NA, Inc.
545 E. Algonquin Road, Ste H., Arlington Heights, IL 60005 USA
Phone: 847-439-5667 Fax: 847-439-7320

www.intertek.com

The certificate and schedule are held in force by regular annual surveillance visits by Intertek Testing Services NA, Inc. and the reader or user should contact Intertek to validate its status. This certificate remains the property of Intertek Testing Services NA, Inc. and must be returned to them on demand. This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

LISTING INFORMATION

Product Covered
Strebord 44 core - Single Leaf Door Assembly - 20 Minutes Without Hose Stream - UL 10C

Product Description

Single leaf single acting doorset in wood frame:
Door Leaf core - Strebord Particle Board - 44mm thick
Door frame - Hardwood (minimum density- 650 kg/m^3)
Door frame size --1100mm x 2200mm x 100mm (w x h x jamb depth)
Door leaf size - 1035mm x 2165mm x 45mm (w x h x thk)
Lippings – all edges except the head of the leaf, Hardwood, maximum 8mm thick, minimum density - 650 kg/m^3

Supporting Construction - Masonry Wall

Minimum latch throw - 12mm

Fire Rating
20 Minutes without hose stream rating according to UL 10C (2016).